

SB200 Series



Bearing NO.	Shaft Dia d		Dimensions(mm/in.)								Dynamic load ratings(N)	Static load ratings(N)	Weight(kg)		
	in	mm	Be	D	Bi	r	n	m	G	ds					
SB201-8	CSB201-8	1/2		12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.09	
202-9	202-9	9/16		12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.08	
202-10	202-10	5/8		12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.08	
203-11	203-11	11/16		12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.07	
SB201	CSB201		12	12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.09	
202	202		15	12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.08	
203	203		17	12	40	22	1	6	16	4.5	10-32UHF M5 X 0.8	780	454	0.07	
SB204-12	CSB204-12	3/4	20	14	47	25	1.5	7	18	4.5	1/4-28 M6 X 0.75	1010	630	0.12	
SB204	CSB204	3/4	20	14	47	25	1.5	7	18	4.5	1/4-28 M6 X 0.75	1010	630	0.12	
SB205-14	CSB205-14	7/8		15	52	27	1.5	7.5	19.5	5	1/4-28 M6 X 0.75	1100	710	0.18	
205-15	205-15	15/16 1		15	52	27	1.5	7.5	19.5	5	1/4-28 M6 X 0.75	1100	710	0.17	
205-16	205-16	15/16 1		15	52	27	1.5	7.5	19.5	5	1/4-28 M6 X 0.75	1100	710	0.16	
SB205	CSB205		25	15	52	27	1.5	7.5	19.5	5	1/4-28 M6 X 0.75	1100	710	0.17	
SB206-17	CSB206-17	1-1/16		16	62	30	1.5	8	22	5.5	1/4-28 M6 X 0.75	1550	1020	0.28	
206-18	206-18	1-1/8		16	62	30	1.5	8	22	5.5	1/4-28 M6 X 0.75	1550	1020	0.26	
206-19	206-19	1-3/16		16	62	30	1.5	8	22	5.5	1/4-28 M6 X 0.75	1550	1020	0.25	
206-20	206-20	1-1/4		16	62	30	1.5	8	22	5.5	1/4-28 M6 X 0.75	1550	1020	0.23	
SB206	CSB206		30	16	62	30	1.5	8	22	5.5	1/4-28 M6 X 0.75	1550	1020	0.25	
SB207-20	CSB207-20	1-1/4		17	72	32	2	8.5	23.5	6	5/16-24 M8 x I	2030	1400	0.41	

SB200 Series

207-21	207-21	1-5/16		17	72	32	2	8.5	23.5	6	5/16-24 M8 x I	2030	1400	0.39	
207-22	207-22	1-3/8		17	72	32	2	8.5	23.5	6	5/16-24 M8 x I	2030	1400	0.37	
207-23	207-23	1-7/16		17	72	32	2	8.5	23.5	6	5/16-24 M8 x I	2030	1400	0.35	
SB207	CSB207		35	17	72	32	2	8.5	23.5	6	5/16-24 M8 x I	2030	1400	0.37	
SB208-24	CSB208-24	1-1/2		18	80	34	2	9	25	8	5/16-24 M8 x I	2300	1600	0.48	
208-25	208-25	1-9/16		18	80	34	2	9	25	8	5/16-24 M8 x I	2300	1600	0.45	
SB208	CSB208		40	18	80	34	2	9	25	8	5/16-24 M8 x I	2300	1600	0.45	
SB209-26	CSB209-26	1-5/8		19	85	41.2	2	10.2	31	8	5/16-24 M8 x I	2570	1810	0.8	
209-27	209-27	1-11/16		19	85	41.2	2	10.2	31	8	5/16-24 M8 x I	2570	1810	0.8	
209-28	209-28	1-3/4		19	85	41.2	2	10.2	31	8	5/16-24 M8 x I	2570	1810	0.8	
SB209	CSB209		45	19	85	41.2	2	10.2	31	8	5/16-24 M8 x I	2570	1810	0.8	
SB210-30	CSB210-30	1-7/8		20	90	43.5	2	10.9	32.6	9	5/16-24 M8 x I	2760	2010	0.87	
210-31	210-31	1-15/16		20	90	43.5	2	10.9	32.6	9	5/16-24 M8 x I	2760	2010	0.87	
SB210	CSB210		50	20	90	43.5	2	10.9	32.6	9	5/16-24 M8 x I	2760	2010	0.87	
SB211-32	CSB211-32	2		21	100	45.3	2.5	11.8	33.5	10	5/16-24 M8 x I	3400	2550	1.1	
211-35	211-35	2-3/16		21	100	45.3	2.5	11.8	33.5	10	5/16-24 M8 x I	3400	2550	1.1	
SB211	CSB211		55	21	100	45.3	2.5	11.8	33.5	10	5/16-24 M8 x I	3400	2550	1.1	
SB212-36	CSB212-36	2-1/4		22	110	53.7	2.5	14.9	38.8	10	3/8-24 M10X1.25	4100	3150	1.3	
212-39	212-39	2-7/16		22	110	53.7	2.5	14.9	38.8	10	3/8-24 M10X1.25	4100	3150	1.3	
SB212	CSB212		60	22	110	53.7	2.5	14.9	38.8	10	3/8-24 M10X1.25	4100	3150	1.3	